

SET-UP DIRECTIONS

1. Evaluate Camp Site for Leveling Camper. If needed, use wood blocks under tire to help level camper out. Once Camper is level (or close to level).
2. Detach Chain and Light Plug from Camper to Your Vehicle
3. Unhook Trailer from Vehicle, crank up dolly jack and pull Vehicle out of way.
4. Adjust Dolly Jack so the bubble on the Level is low – just past the line.
5. Drop down two back Stabilizer Jacks. (Some models need a crank and it will be in cupboard just inside of the door or in the trunk of the 10' Camper) Make sure jacks have blocks of wood underneath them.
6. Crank Dolly Jack back up so the front is above the level – just past the line.
7. Drop down two front Stabilizer Jacks. **Do not take tires off ground.**
8. Unlatch Four Latches on Camper
9. Crank Camper Up. It will stop when fully extended. Optional: unzip awning and let roll to the ground before cranking up.
10. Pull out Both Ends of Trailer (Beds)
11. On Outside of Camper Install Bed Support Arms located underneath beds. (Two on Each End)
12. Inside Camper -- Flip Sink Over
13. Flip Ceiling Brace up over bed into position and also the T-Brace
(Be sure to do this first before doing step #14)
14. On Outside, Pull corners of canvas down over bed corners.
15. Fasten Bungie Straps on Outside of Trailer Under Bed Area
16. Drop Screen Door Down from Ceiling into Place
17. Set Up Table
18. Pull Plug Out and Plug into Power Source. This will enable Refrigerator and A/C to operate. (A/C must be plugged into outlet inside camper as well)
- 19. Leaving Power Plug plugged into your vehicle while camping may cause your vehicle battery to go dead.**

TAKE DOWN DIRECTIONS

1. Unplug Power Source and A/C
2. Drop Table Down
3. Put Screen Door Up into Ceiling and Fasten
4. Pull/Close Privacy Curtains on Beds
5. Unfasten Bungie Straps on Outside of Trailer Under Bed Area
6. Outside Camper, Loosen corners of canvas from bed area.
7. Remove Ceiling Braces above Beds & Lay on Beds
8. Flip Sink Over
9. Unfasten Bed Support Arms at Both Ends of Trailer
10. Shove Beds In
11. Tuck In Canvas
12. Crank Down to about 1'
13. Tuck Canvas In Again
14. Drop Top Completely Down
- 15. Put Crank into Storage Bag in Cupboard inside Camper or in Front Trunk**
16. Latch Four Latches
17. Put four Corner Stabilizers Back Up
18. Hook Trailer to Vehicle
19. Attach Chain and Light Plug
20. Crank up Fifth Wheel and Swivel into Travel Position

NOTE: Be sure when storing gear, etc in camper when camper is closed that you do not damage the faucet on the sink that is hanging upside down.